




Projectors... and more!

EIP-WX5000

WXGA Widescreen 3 DLP® Projector

KEY FEATURES: Model EIP-WX5000

- 5200 ANSI Lumens bright, at 90% uniformity, and a 1800:1 contrast ratio.
- WXGA (16:10) resolution. UXGA ~ VGA, MAC and Workstation compatible.
- 3 DLP™ imaging technology delivers a "seamless" high contrast image.
- Power Zoom and Focus Lens . Optional Wideangle and Telephoto lenses.
- Horizontal & Vertical Lens Shift. H, V & Geometric Keystone Correction.
- Dual Lamp System provides redundancy and permits 4 brightness levels.
- Wireless/wired remote. Wireless remote mouse. Mechanical shutter.
- RS-232 System and Network Control Compatible: Built in D-sub 9 and RJ45.
- Smart data compression / expansion, and video scaling. sRGB Compatibility.
- Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
- Converts Interlace video to Progressive scan. 2-3 Pulldown Support.
- Accepts Analog and Digital Video input signals up to 1080p.
- Power Management, Keylock Security, and Custom Warmup Screen options.
- Unique Projector Stack Control and VideoWall Signal Division features.
- 3 Year* Projector Warranty!



EIP-WX5000

Included Accessories: Printed Quick Setup Guide and Owner's Manual. Quick Setup Guide, Owner's Manual and CAD Drawings on CD ROM. 6.0 ft (1.8 M) AC Power Cord . Lens Cover. VGA-type Computer Input Cable (D-sub 15). Wireless/wired Remote with Mouse Control & 2 x AA batteries. Remote Mouse Receiver on 5.25 ft (1.6M) USB-A cable.

Optional Accessories: Replacement Lamps. Wideangle and Telephoto Lenses. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate.

SPECIFICATIONS: Model EIP-WX5000

Screen Brightness	up to 5200 ANSI Lumens	Video: Resolutions Supported	
Illumination Uniformity	90%	SDTV (Composite, S-Video, Component)	480i / 540p, 576i
Size of Color Palette	8-Bit/16.7 Million	EDTV (DVI w/HDCP)	480p, 576p
Contrast Ratio	1800:1	HDTV (DVI w/HDCP)	720p (60), 1035i (60), 1080i/p (50/60)
Horizontal Resolution	550 TV Lines (HDTV)	Signal Inputs:	
Projection Lamp	280 Watt UHP x 2	HDMI	HDMI x 1
Estimated Lamp Life	up to 3000 Hours of Use	DVI-D(w/HDCP)	DVI-D x 1
Imaging System	0.65" DDR 3 DLP® DMD®	plus Audio: Stereo:	MiniStereo x 1
Screen Pixels	1,024,000 (1280x800) in stripe configuration	Computer/Component 1:	D-sub 15 x 1
Lens Type	Power Zoom and Focus	plus Audio: Stereo:	MiniStereo x 1
Lens Specs	Speed: f:2.5; FL: 1.00~1.26in. (25.5~32.0 mm)	Computer/Component 2:	BNC x 5
Lens Ratios	Zoom Max:Min: 1.25:1; Throw:Width: 1.8~2.5:1	plus, Audio: Stereo:	MiniStereo x 1
Image Diagonal	60~280 in. (152.4~711.2 cm)	S-Video	S-Video x 1
Image Width	4.2~19.8 ft. (1.3~6.03 m.)	plus, Audio: Stereo:	MiniStereo x 1
Throw Distance	7.9~45 ft. (2.4~13.7 m.)	Composite	RCA x 1
Front Elevation / Maximum Pitch	up to 5° up / 9° off the horizontal	plus, Audio: Stereo:	MiniStereo x 1
Vertical Anti Keystone	Power Lens Shift (Top:Bottom) ±66%	Outputs	
Horizontal Anti Keystone	Power Lens Shift (L:R~R:L) ±35%	Computer/Component	D-sub 15 x 1
Vertical Keystone Correction	Digital: 40° up or down	Audio: Line	Stereo: MiniStereo x 1
Horizontal Keystone Correction	Digital: 30° left or right	Audio: Amplifier	Stereo: 3 Watts
Geometric Keystone Correction	Digital	Audio: Built In Speakers	Stereo: 1.3x2.6in. (3.38x6.8 cm) (oval) x 2
Scanning Frequency	Auto: H Sync. 15-126 kHz; V Sync. 43-200 Hz	Operating Noise	as low as 34 dBA
Dot Clock	12~230 MHz	Cabinet Size (HxWxD)	7.5 x 19.7 x 25.1 in. (190 x 500 x 637 mm.)
Image Orientation	Normal, Reversed, Inverted	Weight	58.4 lbs. (26.5 kg)
Local Control / Power Management	Full Function / Auto Shut-Off	Packaged Size	15.8 x 28.4 x 34.3 in. (400 x 720 x 870 mm.)
Remote Projector Control (with Mouse)	Wireless/wired x 1	Packaged Weight	77.2 lb (35 kg)
Wired Remote Port	MiniStereo x 1	Power Requirements	100-240V AC, 50/60Hz
RS-232 Port	Dsub 9-pin x 1	Power Consumption	up to 755 W
LAN Port	RJ45 x 1	Heat	up to 2578 BTU/hr. (649Kcal/hr)
Computer Native Resolution	1280x800 (WXGA)	Power Cord	6' (1.8M) Type 3, Detachable
Computer: Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA	Electrical Safety Compliance	UL / cUL IEC
.....	MAC & Workstation	Electromagnetic Compatibility	FCC Part 15 Class A, CE Mark
Computer: Formats	1600 x 1200 through 640 x 480	Security Facilities	Kensington® Security Slot
Computer: Image Sizing	Normal, or Smart Compressed or Expanded	Operating Temperature	41~104°F (5~40°C)
Video: Color Systems	NTSC/PAL/SECAM/NTSC 4.43 / PAL-M&N	User Maintenance	Clean Air Filter, Replace Lamp
Video: Aspect Ratios Supported	4:3 & 16:9	Warranty (to original end use customer)	
Video: Image Sizing	Video Scaling Technology	Projector :	3 Yr. / 6000 Hr. *(Parts & Labor to Correct Defects)
		Lamp:	90 Days (Failed Lamp Replaced Pro-Rata)
			* Whichever occurs first

Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws.

Specifications subject to change without notice. ©2008 Eiki International, Inc. Issued June 15, 2008.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com

Visit our World Wide Web site: <http://www.eiki.com>